FCI

Explosion-proof Indicator Panel
FCI series for Hazardous Location



Protection Grade

Ex d ⅡB+H2 T6 IP65 for Zone 1·2


Standard Material

- **Body :** Cast Aluminium Alloy
- **Cover :** Cast Aluminium Alloy
- **Indicate Glass :** Heat Resistant Hard Glass
- **Bolt & Washer :** Stainless Steel
- **Unit :** PB,S/S,EM,PL(Red,Green,Yellow).BZ Indicator,Frequency
- **Tamb** : -20°C ≤ Ta ≤ +50°C

Standard Color

- Munsell no. 7.5BG 6/1.5
  If you want other color, contact us please.

Drawing



Dimension(mm)

Model No.	Width(A)	Height(B)	Depth(C)	Mount(D)	Mount(E)
FCI-1*	300	200	215	210	240
FCI-2**	400	300	220	295	352
FCI-4****	400	500	230	455	400
FCI-600	220	250	160	260	170
FCI-3020	300	200	215	210	250
FCI-3040	300	400	220	346	300
FCI-4030	400	300	220	295	352
FCI-5040	400	500	230	455	400
FCI-5040D	500	400	230	400	450
FCI-6030	600	300	285	500	346
FCI-6040	600	400	230	495	450